


0014150	DATA SHEET	
valid from: 15.01.2024	ÖLFLEX® CLASSIC 100 H	

Application

ÖLFLEX® CLASSIC 100 H are halogen free, highly flame retardant, oil resistant power cables for occasional flexible use and fixed installation subject to medium mechanical load conditions. They are among others designed for use in dry and humid conditions. If using outdoors, observe the indicated temperature range and use with UV protection.

They are suitable for occasional, non-automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

Application range:

Public buildings, airport, railway station, plant engineering, industrial machinery, heating and air-conditioning systems and particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards.

Design

Design	based on EN 50525-3-11 EN 50525-2-31 EN 50525-2-51
Conductor	fine wire strands of bare copper acc. to IEC 60228 resp. EN 60228, class 5
Insulation	halogen free compound TI6, acc. to EN 50363-7, with increased requirements
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor up to 5 cores: coloured acc. to VDE 0293-308 resp. HD 308 S2
Stranding	cores are stranded in layers
Outer sheath	halogen free compound TM7, acc. to EN 50363-8, with increased requirements colour: Silver Grey, similar RAL 7001

Electrical properties at 20 °C

Nominal voltage	EN U ₀ /U: fixed and protected installation:	450/750 V 600/1000 V
Test voltage	core / core:	4000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: fixed installation:	15 x outer diameter 4 x outer diameter
Temperature range	occasional flexing: fixed installation:	-30 °C up to +70 °C max. conductor temp. -40 °C up to +80 °C max. conductor temp.
Torsional stress	in WTG: TW-0 (5.000 cycles at ≥ +5 °C) TW-2 (2.000 cycles at ≥ -40 °C) ± 150 °/m at 1 revolution per minute	
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2 no flame-propagation acc. to IEC 60332-3-24 resp. EN 60332-3-24 or acc. to IEC 60332-3-25 resp. EN 60332-3-25	
Halogen free	acc. to IEC 60754-1 resp. EN 60754-1	
Corrosivity of gases	acc. to IEC 60754-2 resp. EN 60754-2	
Smoke density	acc. to IEC 61034-2 resp. EN 61034-2	
Toxicity	acc. to EN 50306-1 (≤ 6)	
Ozone resistance	acc. to EN 50396, method B	
Oil resistance	acc. to EN 50363-4-1 (TM5)	


Tests acc. to IEC 60811 resp. EN 60811, EN 50395, EN 50396

General requirements These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive).

A part of these cables (see www.lappkabel.com/cpr) are classified in accordance with the EU-Regulation no. 305/2011 (CPR).

Environmental information These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: MAIH / PDC	Document: DB0014150EN	Page 1 of 2
Released: ALTE / PDC	Version: 04	

0014150	DATA SHEET	
valid from: 15.01.2024	ÖLFLEX® CLASSIC 100 H	

Creator: MAIH / PDC	Document: DB0014150EN	Page 2 of 2
Released: ALTE / PDC	Version: 04	