

**UNITRONIC® LAN 200 U/UTP Cat. 5e Y**  
**4x2xAWG 24/1****DB2170125**  
valid from: 02.02.2012**Application**

Data cable for transmission of digital and analog signals up to 200 MHz. The cable is designed for horizontal cabling systems as connection between a floor distribution and the telecommunication outlets (TO's). According to TIA/EIA-568-A, ISO/IEC 11801 2<sup>nd</sup> edition, EN 50173, EN 50288-3-1, IEC 61156-5. For application in LANs like IEEE 802.3: 10Base-T, 100Base-T, 1000Base-T; FDDI; ISDN; ATM.

**Design**

Conductor	bare copper AWG 24/1, massive
Insulation	PE, ca. 0.96 mm core Ø
Core identification code	acc. to IEC 708-1
Stranding	4 pairs, stranded to bundle
Outer sheath	PVC, grey similar to RAL 7035, outer diameter: ca. 5.4 mm

**Electrical properties at 20° C**

Resistance (loop)	max. 190 Ω/km, acc. to VDE 0812
Insulation resistance	min. 5 GΩxkm
Mutual capacitance	nom. 50 nF/km
Characteristic impedance	100 Ω ±5 Ω (at 100 MHz)
Velocity of propagation	ca. 0.67 c
Signal propagation time	<510 ns/100m
Delay difference	<20 ns/100m
Test voltage	700 V (AC)

**Transmission properties**

f [MHz]	Attenuation nom. [dB/100m]	NEXT nom. [dB]	ACR nom. [dB/100m]	ELFEXT nom. [dB/100m]	RL nom. [dB]
1	1.8	80	78.2	65	23
4	3.7	75	71.3	56	27
10	5.9	70	64.1	45	30
16	7.4	68	60.6	41	30
20	8.3	65	56.7	39	30
31.25	10.3	60	49.7	35	30
62,5	14.4	56	41.6	30	30
100	19.2	52	32.8	25	28
155	22.1	47	24.9	23	26
200	24.8	44	20.2	21	24

**UNITRONIC® LAN 200 U/UTP Cat. 5e Y  
4x2xAWG 24/1**DB2170125  
valid from: 02.02.2012**Mechanical and thermal properties**

Minimum bending radius	during installation: 8 x cable Ø static: 4 x cable Ø
Permissible temperature range	during installation: 0 ° C up to +50 ° C static: -20 ° C up to +60 ° C
Flame propagation	flame retardant acc. to IEC 60332-1-2
General requirements	Dangerous and forbidden substances acc. to RoHS directive (2002/95/EG) are not allowed to the manufacturing.