

OTM

Fast-Acting Midget Fuses

MIDGET, PC MOUNT & MINIATURE FUSES

M
F



One-time OTM midget fuses provide low-cost protection for 250 volt AC general purpose lighting, heating, control circuits, etc. where time-delay is not required. (Not for Branch Circuit Protection).

FEATURES/BENEFITS:

- Low cost and fully rated for economy without compromise
- Can be used with UltraSafe™ fuse holders
- 1 1/2" x 13/32" (10 mm x 38 mm) dimensions

CATALOG NUMBERS (AMPS)

| | | | | | |
|------|------|------|-------|-------|-------|
| OTM1 | OTM3 | OTM5 | OTM8 | OTM15 | OTM25 |
| OTM2 | OTM4 | OTM6 | OTM10 | OTM20 | OTM30 |

RECOMMENDED FUSE BLOCKS for Midget (10x38mm) Fuses

| Number of Poles | Catalog Number | | | |
|-----------------|-----------------------------------|-----------------|--------------------------|----------------------|
| | UltraSafe™ Indicating Fuse Holder | Screw Connector | Pressure Plate Connector | Copper Box Connector |
| Adder | | 30310 | 30320 | 30350 |
| 1 | USM11 | 30311 | 30321 | 30351 |
| 2 | USM21 | 30312 | 30322 | 30352 |
| 3 | USM31 | 30313 | 30323 | 30353 |
| 3 | USFM10I | | | |

RATINGS:

- **Volts:** 250VAC
- **Amps:** 1 to 30A
- **I.R.:** 10kA I.R.

HIGHLIGHTS:

- Fast-acting

APPLICATIONS:

- Supplemental protection of circuits up to 250VAC and 10kA

APPROVALS:

- UL Listed to standard 248-14, File E33925
- CSA Certified to Standard C22.2 No. 248.14

